

Commercial MIL-DTL-5015

Dust Caps & Rubber Bushing

- Dust cap with external thread for use with Straight Plugs (M90-3106F).
- Dust cap with internal thread for use with Cable connectors (M90-3101F) and Panel Mount connectors (M90-3102R).
- Dust caps supplied fitted with chain.
- Rubber Bushing for use with Cable connectors (M90-3101F).



DUST CAP – EXTERNAL THREAD		RUBBER BUSHING																					
CALCULATION <table border="1"> <thead> <tr> <th>SIZE</th><th>THREAD</th><th>ØA max</th><th>B max</th><th>C</th></tr> </thead> <tbody> <tr> <td>10SL</td><td>5/8-24UNEF-2A</td><td>17.45</td><td>16.66</td><td>101.60</td></tr> <tr> <td>12S</td><td>3/4-20UNEF-2A</td><td>20.62</td><td>21.44</td><td>114.30</td></tr> <tr> <td>14S</td><td>7/8-20UNEF-2A</td><td>23.80</td><td>21.44</td><td>114.30</td></tr> </tbody> </table>		SIZE	THREAD	ØA max	B max	C	10SL	5/8-24UNEF-2A	17.45	16.66	101.60	12S	3/4-20UNEF-2A	20.62	21.44	114.30	14S	7/8-20UNEF-2A	23.80	21.44	114.30		
SIZE	THREAD	ØA max	B max	C																			
10SL	5/8-24UNEF-2A	17.45	16.66	101.60																			
12S	3/4-20UNEF-2A	20.62	21.44	114.30																			
14S	7/8-20UNEF-2A	23.80	21.44	114.30																			
DUST CAP – INTERNAL THREAD		CALCULATION <table border="1"> <thead> <tr> <th>SIZE</th><th>THREAD</th><th>ØA max</th><th>C</th></tr> </thead> <tbody> <tr> <td>10SL</td><td>5/8-24UNEF-2B</td><td>20.70</td><td>101.60</td></tr> <tr> <td>12S</td><td>3/4-20UNEF-2B</td><td>25.40</td><td>114.30</td></tr> <tr> <td>14S</td><td>7/8-20UNEF-2B</td><td>28.57</td><td>114.30</td></tr> </tbody> </table>		SIZE	THREAD	ØA max	C	10SL	5/8-24UNEF-2B	20.70	101.60	12S	3/4-20UNEF-2B	25.40	114.30	14S	7/8-20UNEF-2B	28.57	114.30				
SIZE	THREAD	ØA max	C																				
10SL	5/8-24UNEF-2B	20.70	101.60																				
12S	3/4-20UNEF-2B	25.40	114.30																				
14S	7/8-20UNEF-2B	28.57	114.30																				
		CALCULATION <table border="1"> <thead> <tr> <th>SIZE</th><th>ØA</th><th>B</th></tr> </thead> <tbody> <tr> <td>4</td><td>5.59</td><td>69.85</td></tr> <tr> <td>6</td><td>7.92</td><td>66.68</td></tr> </tbody> </table>		SIZE	ØA	B	4	5.59	69.85	6	7.92	66.68											
SIZE	ØA	B																					
4	5.59	69.85																					
6	7.92	66.68																					
HOW TO ORDER																							
25042 Dust Cap – External thread		C90 - XXXXX - XXXX																					
25043 Dust Cap – Internal thread		SIZE <table border="1"> <tbody> <tr> <td>10SL</td><td>For use with 10SL shell size (Dust caps)</td></tr> <tr> <td>12S</td><td>For use with 12S shell size (Dust caps)</td></tr> <tr> <td>14S</td><td>For use with 14S shell size (Dust caps)</td></tr> <tr> <td>4</td><td>For use with 10SL & 12S shell sizes (Bushing)</td></tr> <tr> <td>6</td><td>For use with 14S shell size (Bushing)</td></tr> </tbody> </table>		10SL	For use with 10SL shell size (Dust caps)	12S	For use with 12S shell size (Dust caps)	14S	For use with 14S shell size (Dust caps)	4	For use with 10SL & 12S shell sizes (Bushing)	6	For use with 14S shell size (Bushing)										
10SL	For use with 10SL shell size (Dust caps)																						
12S	For use with 12S shell size (Dust caps)																						
14S	For use with 14S shell size (Dust caps)																						
4	For use with 10SL & 12S shell sizes (Bushing)																						
6	For use with 14S shell size (Bushing)																						
3420 Rubber Bushing																							

All dimensions in mm.